

DATA SHEET

Display SL 3260W

Issue: October 2009

Advanced Display: 64.9 cm (25.5-inch) widescreen
Lifestyle design and entertainment features

The Display SL3260W offers superb multimedia and office performance at a very attractive price. It comes in a trendy design with glossy black front and offers stunning advanced contrast ratio (ACR) 20,000:1, 2 x HDMI, D-SUB and DVI via cable in 16:10 format. Something special is the Lifecycle Extender. The SL3260W fits perfectly into your office or home environment and can also replace your TV set.

Maximum resolution 1920 x 1200 for ultimate entertainment experience

Fast response time of 2 ms for gaming, internet, office, multitasking and more


64.9 cm (25.5-inch) widescreen display in optimum 16:10 format

Highly flexible with S/PDIF out, 2 x HDMI (w/ HDCP), D-Sub and DVI via cable

Energy Star 5.0 compliant: 34 W typical power consumption and power management according to EPA 5.0

Lifetime extender and theme mode for optimized picture

Due to integrated speakers and HDMI cable no further accessories needed



Display SL 3260W

Special features

ECO Status LED: 3 colors for 3 modes, Lifetime Extender, Screen ratio conversion

Stand removable

Tilt angle + 5° / - 15°

Picture performance

Contrast - advanced 20,000:1

Response time gray to gray 2 ms typical

Viewing angle (h/v) 170° / 170°

Color performance 16.7 Mio colors (Hi-FRC)

Brightness - typical 300 cd/m²

Size and resolution

Aspect ratio 16:10

Diagonal Size 64.9 cm (25.5-inch)

Resolution (native) 1920 x 1200 pixel (recommended)

Resolution (interpolated) 1920 x 1080 pixel, 1680 x 1050 pixel, 1440 x 900 pixel, 1280 x 1024 pixel

Video modes 1080i/p, 720i/p, 576i/p, 480i/p

Picture size 550.1 x 343.8 mm

Pixel Pitch 0.287 mm

Frequencies

Horizontal 31.5 kHz - 82 kHz

Horizontal analog 31.5 kHz - 82 kHz

Horizontal digital 15kHz - 82 kHz

Vertical 56 - 76 Hz

Frequencies - bandwidth 210 MHz

Connectivity

Video input 2 x HDMI, 1 x D-SUB

Audio sound output 2 x 2.0 W

Audio signal input 3.5 mm stereo phone jack

Audio signal output S/PDIF (optical)

HDMI audio Yes

OSD Languages and setting options

Languages Czech, Danish, Dutch, English, Finnish, French, German, Hungarian, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish

Brightness / Contrast Brightness, Contrast

Color Cold, Warm, Custom Color

Image adjust Clock, H-Position, V-Position, Expansion

Audio Mute, Volume

Information Resolution/mode, Signal input

Mode General, Movie, Picture, Game

Power consumption (typical, w/o sound)

Soft switch off 0.7 W

Power save mode 0.8 W

Operating with EPA settings 34 W

Operating maximum brightness 45 W

Electrical values

Rated voltage range 100 - 240 V

Rated frequency range 50 - 60 Hz

Protection class 1

Compliance

Europe CE, TCO Displays 5.0

Compliance

USA/Canada	FCC Class B, cUL
Australia/New Zealand	C-Tick
Russia	GOST
Saudi Arabia	SASO
Global	ENERGY STAR® 5.0, ISO9241-307 (Pixel fault class I), IT-Eco-Declaration, RoHS, WEEE
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Quality and Reliability

MTBF (demonstrated)	50.000 h
---------------------	----------

Dimensions / Weight / Environmental

Dimension without stand (W x D x H)	603.72 x 138.8 x 413 mm
Dimension with stand (W x D x H)	603.72 x 238.7 x 475.5 mm
Weight (packed)	10.5 kg
Weight (unpacked)	8.5 kg
Weight (Monitor only)	
Operating ambient temperature	5 - 35°C

Miscellaneous

VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock

Package content

Data cable 1.8m, HDMI (19-pin), Data cable 1.8m, D-SUB (15-pin), Audio cable 1.8m, Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8m, User manual, Warranty booklet, Quickstart flyer

Order information

Order Code	S26361-K1328-V160
EAN-Nr.	4049699094965

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:

<http://ts.fujitsu.com/aboutus>

Take back and Recycling information:

<http://ts.fujitsu.com/recycling>

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions October 2009

Published by
Fujitsu Technology Solutions
<http://ts.fujitsu.com>